

SILKWOOD

The Superior Choice

+27 {012} 668-1069

@silkwoodafrica

@silkwoodafrica



www.silkwoodafrica.com

Correct Application Directions For Silkwood M2 Use

Typical Applications

- Garage Doors (Interior & Exterior)
- Wooden Fencing
- Log Cabins (Interior & Exterior)
- Wendy Houses (Interior & Exterior)
- Window Frames
- Outdoor Furniture
- Log Poles
- Wooden Doors (Interior & Exterior)
- Wooden Gates
- Jungle Gyms
- Lapa/Gazebo (Interior & Exterior)



M2 APPLICATION CRITERIA

- There is no need to dilute the M2 product range with mineral turpentine, this should only be done for the M7 product range.
- The surface to be dry, clean and free of all contaminants, e.g. previous paints or varnishes.
- The surface should be well sanded, down to the bare grain to get excellent results.
- We recommend maintenance of X 2 coats every 8 months for the first 3 years.
- The product can be spray or brush applied.

Silkwood will give you 10-12 m² per litre.

- An initial coating followed by at least two successive coats should be applied. X3 recommend coats should be applied to your application.

Adequate drying should take place between coats, you should allow 24-28 hours drying per coat.

- If the surface has a fluffy appearance it should be rubbed with either a scotchgard, pad or steel wool prior to coating.
- The drying time can vary depending upon the ambient temperature and humidity.
- For optimal results, all surfaces including the end grain should be coated.

- To get the best results using Silkwood's product range when applying it should be done so in a sparingly motion and not just blotched on and painted.
- Do not expose the product to naked flames etc, as it is flammable.

Specific Characteristics

Physical Appearance: Pale Yellow Liquid

S.G: 0.84

Solid (Mass): 46.0

Spread Rate: Approx 10-12 mt per litre, depending upon density and porosity of the wood.

* **Under no circumstances should M2 product range be mixed with any mineral turps, it should only be used for the M7 colour range including clear, do not add any stains or colourants to Silkwood product range, as it will not work we have specific colours that have added pigments to give you the colour you want.**

